

STARDROP / DARKWAY

PENDANT DIRECT

The stardrop is quite adaptable to well integrate into the space ratio and requirements. The stardrop device can be either ceiling mounted or pendant. The number of spots can be modified in every unit. This product offers high visual comfort, ideal for residential and commercial spaces.

- Clean square light distribution from 25mm round aperture reflectors. The optimal beam angle over field angle ratio offers a highly-uniform horizontal surface
- Flexibility of mounting height with 3 beam angles
- Homogeneous color mixing within one reflector



Luminaire


Application: Ambient
Body Material: Extruded aluminium

Optics


Optic Type: Special Reflector With Microfaceted Surface
Glare Control Device: Cinco Cell Baffles
Surface Diffuser: No Diffuser

Electrical equipment


Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%




Polar Curves



Narrow Beam 36° LOR:
70.3%



Medium Beam 50° LOR:
90.4%



Wide Beam 60° LOR: 88.5%

We reserve the right to make technical changes without prior notice

STARDROP / DARKWAY

PENDANT DIRECT

Code Index:

<u>S</u> <u>D</u>	<u>I</u>	<u>P</u> <u>D</u>	<u>R</u>	<u>1</u>	<u>D</u>	<u>---</u>	<u>-----</u>	<u>-</u>	<u>2</u> <u>0</u>	<u>---</u>	<u>I</u>	<u>2</u> <u>0</u>
Family	Environment	Mounting	Shape	Number of LED	Optic	Light Distribution	CRI/CCT & Power	Control	IP	Body Finish	Layout	Length
						SN	927E1	J		BS		
						SM	927E2	K		BT		
						SW	927E3	L		WS		
							930E1			WT		
							930E2			GS		
							930E3					
							940E1					
							940E2					
							940E3					

Family
SD Stardrop

Environment
I Indoor

Mounting
PD Pendant Direct

Shape
R Round

Number of LED
11 LED

Optic
D Darkway

Light Distribution
SN Narrow Beam, 36°
SM Medium Beam, 50°
SW Wide Beam, 60°

CRI/CCT & Power

	LED Load	initial Lumen
2700°K	927E1: 1 W	100 lm
	927E2: 1.5 W	140 lm
	927E3: 2 W	180 lm
3000°K	930E1: 1 W	110 lm
	930E2: 1.5 W	150 lm
	930E3: 2 W	190 lm
4000°K	940E1: 1 W	110 lm
	940E2: 1.5 W	150 lm
	940E3: 2 W	200 lm

Control
J Non-dimmable
K DALI Dimmable
L 1-10V Dimmable

IP
20 IP20

Body Finish
BS Black Smooth
BT Black Fine Textured
WS White Smooth
WT White Textured
GS Gray Smooth

Layout
I I Shape

Length
20 20 cm

We reserve the right to make technical changes without prior notice